

BOHA!®

TERMINAL 2

DRIVE OPERATIONAL EXCELLENCE WITH A PURPOSE-BUILT SOLUTION

BOHA!® Terminal 2 is the proven platform for streamlining foodservice operations. It replaces manual processes with digital precision — helping teams label faster, more accurately, and in full compliance with food safety standards. From grab 'n go to date code automation, this high-performance device delivers measurable labor savings, reduces risk, and improves consistency across every shift. Featuring cloud-based controls, an intuitive touchscreen, and best-in-class print quality, BOHA! Terminal 2 is engineered to perform in the most demanding back-of-house environments.



FEATURES & SPECIFICATIONS



Cloud Management

Make and deploy updates across all or a selection of locations at a click of a button



Label Flexibility

Print 1" - 3" wide labels with drop-in paper loading convenience. Prints at 300 dpi for crisp, easy-to-read labels.



Print On-Demand

The BOHA!® Terminal 2 has the fastest print start time yet - a 47% improvement from the original terminal. Labels print instantly at 5 inches per second.

Print Mechanisms	2
Print Resolution	300 dpi
Max Print Zone	3.15" (80 mm)
Print Speed	5 ips (127 mm/sec)
Print Head Life	31.07 miles (50 km), 43.45 miles (70 km) with TransAct Approved Paper
Paper Path	Open
Label Types	Direct Thermal, Die Cut Direct Thermal, Continuous w/Liner, Receipt
Label Position Detection	Gap sensing
Maximum Label Roll Diameter	4.5" (114.3 mm)
Maximum Label Length	22" (560 mm)
Label Width	1" - 3" wide, fully adjustable
Wall Mount	Optional
Screen Size	10.95"
Screen Resolution	1920x1200
Screen Touch Type	Capacitive Touch

Additional Support

Third Printer Support (including the TransAct M9000) Scanner Support Mi-Fi Support

Communications

Wi-Fi 802.11ac Bluetooth 5 Bluetooth Low Energy (BLE) LTE (US Only)

Network

Wi-Fi, Ethernet (Up to 100Mbps), LTE (US only)

USB Data Ports

2 USB 2.0 High-Speed Ports

RAM/Storage

8GB / 128GB eMMC

Main Power Supply

Internal, 90-250 VAC, 50/60Hz

Auxiliary Power Out

24 VDC

Dimensions

11.6" W x 10.0" D x 9.7" H
294 mm W x 256 mm D x 246 mm H

Weight

8.05 lbs (3.65 kg)

Operating Temperature

5-40° C, 10-90% RH

Compliance

SAFETY: UL/EN 62368-1:2014
EMC: FCC, ICES, CE, UKCA
WIRELESS: FCC, IC

Warranty

1 Year Standard Warranty



©2026 TransAct Technologies Incorporated.
All rights reserved. TransAct® and BOHA!®
are registered trademarks of
TransAct Technologies Incorporated.



Learn More Here

Contact Us

Online: transact-tech.com

Call: 844-243-2228

Email: boha@transact-tech.com